Step By Step Procedure for Grill Start Up & Shut Down

Safety reminders: Never light the grill with the lid closed. Keep face and hands away from the grill when igniting. If you smell gas, turn everything OFF and wait before retrying.

1. Check the grill - Make sure the grill lid is **open**. - Ensure the control knobs are turned **OFF**.	
2. Safety Auto Shut-Off Gas Timer - Rotate Safety Auto Shut-Off Gas Timer Clockwise to your estimated minutes of grilling time. (Note if additional time is needed during grilling just rotate timer for added time)	 
3. Turn on the propane - Slowly open the propane tank valve by turning it **counterclockwise**. - Open it all the way, then pause **5–10 seconds** to let gas flow.	

4. Ignite the grill - Turn photo identified **burner knob** to the **FLAME ICON.** You should hear a clicking sound and see a **flame light**. Once burner lights rotate knob to desired setting. - If the burner doesn't light within **5 seconds**, turn the knob OFF, wait **1 minute**, and try again. - Once the inital burner is lit, turn on the remaining burners as needed to your desired setting. They should light automatically from the first burner.	

After Grilling: Shutdown & Cleanup

1. Burn off residue Before shutting everything down completely, turn burners to HIGH for 3–5 minutes to burn off food residue.
2. Turn off the burners Turn all burner control knobs to OFF
3. Turn off the propane Close the propane tank valve by turning it clockwise until it is fully closed**.**
4. Clean the grill grates Use a grill brush to remove food and grease from the grates. Once cooled, if needed, wipe grates with a damp cloth or paper
5. Clean the surrounding area Pick up food scraps, utensils, and trash. Wipe down the side shelves and nearby surfaces. Ensure the area is free of grease drips or spills.
6. Final Safety Check Confirm all knobs are OFF. Confirm the propane tank valve is fully closed. Make sure no flames or hot surfaces remain before leaving the area.